

1. (Currently Amended) A roller blind for motor vehicles,

comprising

a winding shaft (6),

a mounting arrangement (5) for mounting the winding shaft (6) with variable
alignment,

a blind (7) that is windable on the winding shaft (6), and

in a region of each end of the winding shaft (6), a respective spring means (15),
arrangeable stationary relative to the motor vehicle, and engaging in a region of
the respective winding shaft end, for automatic alignment of the winding shaft (6),
wherein

the mounting arrangement (5) has, in a region of each spring means (15), a
respective moveable bearing (11) for moveable mounting in a direction
substantially parallel to a pulling direction of the blind (7), for moveable
mounting of the respective winding shaft end, and wherein each moveable bearing
(11) comprises a retaining element (12) with a bore for receiving a winding shaft
(6) and a guide device (19) that is displaceably engaged with a guide member (20)
arrangeable stationary of the motor vehicle, in a direction substantially parallel to
the pulling direction of the blind (7).
2. (Cancelled)
3. (Currently Amended) The roller blind according to claim [[2]] 1, wherein the

guide member (20) comprises a substantially elongate rail.

4. (Currently Amended) The roller blind according to claim [[2]] 1, wherein the guide device (19) comprises a groove extending substantially parallel of the guide member (20).
5. (Currently Amended) The roller blind according to claim [[2]] 1, wherein the retaining element (12) has a receiving device (21) for receiving a first end of a spring means (15).
6. (Currently Amended) The roller blind according to claim [[2]] 1, wherein each moveable bearing (11) comprises a base body (13) that is fixably stationary on the motor vehicle and on which the guide member (20) is mounted.
7. (Original) The roller blind according to claim 6, wherein the base body (13) comprises a receiving device (21) for receiving a second end of the spring means (15).
8. (Original) The roller blind according to claim 1, wherein each spring means (15) comprises a spiral spring.
9. (Original) The roller blind according to claim 1, wherein each spring means (15) presses a respective retaining element with an opened roller blind (4) onto a stop (16) on a respective base body (13) substantially against a direction parallel to a pulling direction of the blind (7).
10. (Previously Presented) The roller blind according to claim 1, wherein each spring means (15) holds a respective retaining element (12) with the roller blind (4) closed, at a spacing from a respective stop (16), the distance being determined by a spring stress of the respective spring means (15) and a tension in the blind (7) in a pulling direction of the blind (7).